

The Professional Thermal Solution Provider of

Osram

PrevaLED (Spot lighting/Downlight) Module



Active cooled luminaire designs

6 Advantages


- Small form factor with lower-noise fan
- High efficiency, low power consumption
- Optimized thermal performance, light weight
- Super Silence Fan design, long life
- Dust-resistance System
- High reliability, up to 5 Yr warranty





Model No.	LA004-001A99DN
Module Dimension	φ 86 x 52.5 mm
Weight	231g
Cooling Module Noise @ 1M	15.8dB(A)
Rated Voltage	5VDC
Power Consumption	0.40Watts
Fan Speed	2200 RPM+/- 10%
Heat Sink Material	AL6063
Safety	UL/CUR/TUV/CE
LFP-3000-840-HD-C(39W)	Tc=50 °C @Ta=35°C

1. Tc : Maximum Surface Temperature of LED Module, Ta : Ambient Temperature
2. All specifications were tested in free air.
3. Products or Information are subject to change without notice. Please contact with Sunon Sales.
4. If you have inquiry for TIM, please contact Sunon sales.



Standard function	Optional function
1 Fan Rated Voltage_12V	1 Fan Rated Voltage_5V
2 Auto Restart	2 PWM speed control
3 Reverse Polarity Protection	3 Protection IP 51
	4 Fan 3rd wire signal (F/R type)
	5 Temperature controller