



公差/General tolerances(mm)		公差/General tolerances(mm)										公差/General tolerances(mm)	
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/10
~	~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	~500
3	6	10	18	30	50	80	120	180	250	315	400	500	±2
±0.12 ±0.18 ±0.22 ±0.26 ±0.31 ±0.37 ±0.57 ±0.80 ±0.93 ±1.05 ±1.15 ±1.60 ±2.20 ±2.50													±Z

ITEM	NAME OF PART	MATERIAL	NOTES
3	Current Carrier	Copper	Sn Plated
2	Spring	Stainless Steel	
1	Housing	PA66	UL94V-0

REV	ECN	DESCRIPTION	DRT	DATE
1				

MATERIAL:	/	SURFACE:	/
MAT NO.:	/	宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD	
STATUS:	/		
APPD:	LI GL 2020.05.29	NAME:	WS10-TW-01P-1Y-00A(H)
CHKD:	Mao J 2020.05.29	DRAWING NO.:	WS10-TW-C01
DRT:	Apple 2013.12.05	TYPE:	CUSTOMER DRAWING
SIZE:	A4	SCALE:	1:1
		SHEET	1/1

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	600/50	600/50	600/5
EC 标准/EC Standard:			
过压类别/Overvoltage Category/污染等			
级/Pollution Degree	III/3	/	/
额定电压/电流/Rated Voltage(V)/Current(A)	800/57	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	8	/	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.2~10/24~8		
同距/Pitch(mm)	10.0		
剥线长度/Stripping length(mm)	13-14		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number:	/		
PANTONE / RAL	/		