



Pitch Range In mm		Nominal Dimension Range In mm					
Over	Over	Over	Over	Over	Over	Over	
6	10	10	30	60	100	150	
TO	TO	TO	TO	TO	TO	TO	
6	10	24	30	60	100	150	
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	
						±1.30	
						±2	

5	Transparent cover	PC	UL94V-2
4	Screw	Steel	Zn Plated
3	Pin header	Copper Alloy	Sn Plated
2	Nut	Steel	Zn Plated
1	Housing	PBT	UL94V-0

UL 标准 / UL Standard: B C D

额定电压/电源 / Rated Voltage(V)/Current(A) 600/1000/600/1000 600/75

螺栓扭矩 / Torque Tightening(N·m/Lb·in) M6, 7.9/70.0

线芯范围 (导线) / Wire Range(Flexible)(AWG) 18~3

间距 / Pitch(mm) / 线芯范围 / Poles 20.20/11P

剥线长度 / Stripping length(mm) 18

使用温度范围 / Operating temperature(°C) -40~+120

符合 RoHS 要求 / Conform to RoHS Yes

MATERIAL: /

SURFACE: /

MAT NO.: /

STATUS: /

APPD: /

CHKD: /

DRT: GWG 2019.8.9

NAME: **DEGSON** 宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD

DWG NO.: DG2020-B-C01

REV	ECN	DESCRIPTION	DRT	DATE
1				
2				
3				
4				
5				
6				

DRAWING NO.: DG2020-B-C01

TYPE: CUSTOMER DRAWING

SCALE: 1:2

SHEET 1/1