


cover and housing  
contact by sonic  
welding



公差等级/General Tolerances(mm)	
0	>3
~	>6
3	~6
6	10
10	18
18	30
30	50
50	80
80	120
120	180
180	250
250	315
315	400
400	500
500	~500
~500	>500
±Z	±Z

6	Cap	Copper alloy	M2.5
5	Screw	Steel	M2/Zn Plated
4	Cage	Copper alloy	Ni Plated
3	Pin	Copper	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

UL 标准/UL Standard:	B
额定电压/电涌/Rated Voltage(V)/Current(A)	300/8
IEC 标准/IEC Standard:	III/2
过压类别/Overvoltage Category/污染等级	III/2
额定电压/电涌/Rated Voltage(V)/Current(A)	250/7
工频耐压/Withstanding voltage(V/1Min)	AC2000
拧紧扭矩/Torque Tightening(N·m/Lbin)	M2, 0.2/1.77
线芯范围(硬线和软线)/Wire Range(rigid and flexible)(mm <sup>2</sup> /AWG)	0.2~1.5/30~14
间距/Pitch(mm)/线数范围/Poles	3.81/N=02~16P
引线长度/Stripping length(mm)	5~6
使用温度范围/Operating temperature(°C)	-40~+105
符合RoHS要求/Conform to RoHS	Yes

MATERIAL:	SURFACE:
MAT NO.:	/
STATUS:	/

NAME:	15EDG-GBM-3.81-XXP-1Y-00A(H)
APPD: Lon ChH	2020.06.10
CHKD: Yu JZh	2020.06.10
DRAFT: Li Zh	2020.06.10

DRAWING NO.:	10002260
TYPE:	CUSTOMER DRAWING
SCALE:	2:1
REV	TO
REV	1/1

SIZE: A4	mm
SIZE: A4	inch

D

C

B

A

D

C

B

A