



公差表 (General Tolerances)(mm)													
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/1.0
~	3	~	6	~	10	~	18	~	30	~	50	~	>500
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.47	±0.57	±0.80	±1.05	±1.15	±1.60	±2.20	±2.50
													±Z

3	Screw	Steel	Ni Plated	
2	Pin header	Copper alloy	Sn Plated	
1	Housing	PA66	UL94V-0	
ITEM	NAME OF PART	MATERIAL	NOTES	
UL 标准/UL Standard:		B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)		300/201	300/201	300/10
EC 标准/EC Standard:				
过压类别/Overvoltage Category/污染等级/Pollution Degree		III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)		500/32	600/32	1000/32
额定脉冲电压/Rate Impulse Voltage(KV)		4	6	6
螺丝扭矩/Torque Tightening(N·m/Lb·in)		M4, 1.2/10.53		
线径范围/线径范围(AWG)		22~12		
间距/Pitch(mm)/线数范围/Poles		10.00/N=02~24P		
剥线长度/Stripping length(mm)		9		
使用温度范围/Operating temperature(°C)		-40~+105		
符合RoHS环保要求/Conform to RoHS		Yes		

MATERIAL: / SURFACE: /

MAT NO.: /

STATUS: /

APPD: /

CHKD: /

DRAFT: WU NK 2020.5.27

DRAWING NO.: DG55R-C03

TYPE: CUSTOMER DRAWING

DEGSON® 宁波高松电子有限公司
 NINGBO DEGSON ELECTRICAL CO., LTD

NAME: **DG55R-A-XXP-1Y-00A(H)**
 DRAWING NO.: DG55R-C03
 TYPE: CUSTOMER DRAWING
 SCALE: 1:1
 SHEET 1/1

REV	ECN	DESCRIPTION	DRAFT	DATE

1 2 3 4 5 6