



精度等级/General	tolerance/(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50			

ITEM	NAME OF PART	MATERIAL	NOTES
5	Grounding body	Copper alloy	Sn Plated
4	Cage	Steel	Zn Plated
3	Current carrier	Copper	Sn Plated
2	Screw	Steel	M3/Zn Plated
1	Housing	PA66	UL94V-0

REV	ECN	DESCRIPTION	DRAFT	DATE
1				

MATERIAL: /	SURFACE: /
MAT NO.: /	
STATUS: /	
APPD: Li GL 2020.04.13	NAME: <b>DEGSON</b> 宁波高松电子有限公司
CHKD: Moo J 2020.04.13	<b>NINGBO DEGSON ELECTRICAL CO., LTD</b>
DRAFT: Wang Y 2020.04.13	DRAWING NO.: DC4-PE-01P-1C-00A(H)
	TYPE: CUSTOMER DRAWING
	SCALE: 2:1
	REV T2
	1/1 SHEET

UI 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	/	/	/
IEC 标准/IEC Standard:			
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/特类等	III/3	/	/
额定电压/电涌/Rated Voltage(V)/Current(A)	/	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	8	/	/
额定扭矩/Torque Tightening(N·m/Lb.in)	M3, 0.66/6		
导线范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)	0.5~4/22~10		
厚度/Pitch(mm)	6.1		
剥线长度/Stripping length(mm)	8-9		
使用温度范围/Operating Temperature(°C)	-40~+105		
符合RoHS标准/Conform to RoHS	Yes		
标准颜色编号/Standard color number:			
PANTONE / RAL	/		