



公差等级/General	tolerances/(mm)										公差等级/General	
0	>.3	>.6	>.10	>.18	>.30	>.50	>.80	>.120	>.180	>.315	>.400	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	±Z
3	6	10	18	30	50	80	120	180	250	315	400	500
±0.12 ±0.18 ±0.22 ±0.26 ±0.31 ±0.37 ±0.57 ±0.80 ±1.05 ±1.15 ±1.60 ±2.20 ±2.50												

ITEM	NAME OF PART	MATERIAL	NOTES
3	Current carrier	Copper alloy	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	150/7	/	150/7
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电涌/Rated Voltage(V)/Current(A)	250/6	320/6	630/6
额定脉冲电压(V)/Rate Impulse Voltage(KV)	4	4	4
额定扭矩/Torque Tightening(N.m/Lb.in)			
线径范围(裸线/漆线)/Wire Range(rigid and flexible)(mm <sup>2</sup> /AWG)	0.5~1.0mm <sup>2</sup> (SOL)/22~18 AWG(SOL)		
间距/Pitch(mm)/线数范围/Poles	2.1/02P		
剥线长度/Stripping length(mm)	5~6		
使用温度范围/Operating Temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number:	PANTONE / RAL /		
MATERIAL:	SURFACE: /		

**DEGSON** 宁波高松电子有限公司  
**NINGBO DEGSON ELECTRICAL CO., LTD**

NAME: **DG220B-2.1-02P-1Y-00A(H)**  
 APPD: Li GL 2020.05.30  
 CHKD: /

DWT: MoEK 2020.03.30  
 DRAWING NO.: DG220B-2.1-C17  
 TYPE: CUSTOMER DRAWING  
 SCALE: 5:1  
 SHEET 1/1

REV	ECN	DESCRIPTION	DWT	DATE	SIZE: A4	SCALE: 5:1	REV	SHEET
1	2	3	4	5	6	7	8	9