



公差等级/General Tolerances(mm)		0.1/10	
0	>3	>6	>10
~	3	~	~
3	6	10	18
~	18	30	50
~	50	80	120
~	120	180	250
~	250	315	400
~	400	500	~
~	500	~	~
±0.12	±0.18	±0.22	±0.26
±0.31	±0.37	±0.57	±0.80
±1.05	±1.15	±1.60	±2.20
±2.50	±2.50	±2.50	±2.50

ITEM	NAME OF PART	MATERIAL	NOTES
3	Current carrier	Copper alloy	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

UL 标准 /UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	150/7	/	150/7
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电涌/Rated Voltage(V)/Current(A)	250/6	320/6	630/6
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	4	4	4
额定扭矩/Torque Tightening(N.m/Lb.in)	/	/	/
线径范围(裸线/带涂层)/Wire Range(rigid and flexible)(mm ² /AWG)	0.5~1.0mm ² (SOL)/22~18 AWG(SOL)		
间距/Pitch(mm)/线径范围/Poles	2.1/04P		
剥线长度/Stripping length(mm)	5-6		
使用温度范围/Operating Temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number:	/		
PANTONE / RAL	/		

MATERIAL: / SURFACE: /

MAT NO.: /
 STATUS: /
 APPD: Li GL 2020.05.30
 CHKD: /

NAME: **DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD**
DG220B-2.1-04P-1Y-00A(H)

DRAWING NO.: DG220B-2.1-C01
 TYPE: CUSTOMER DRAWING
 SCALE: 5:1
 SHEET 1/1

REV	ECN	DESCRIPTION	DRAFT	DATE
1				
2				
3				
4				
5				
6				