



精度等级/General	tolerance(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
~	~	3	6	10	18	30	50	80	120	180	250	315	400	500	~	~
±0.12	±0.18	±0.22	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2.50	±2.50	±2	~

UL 标准/UL Standard:	IEC 标准/IEC Standard:	过压类别/Overvoltage Category/行架等级/Pollution Degree	额定电压/电压/Rated Voltage(V)/Current(A)	额定脉冲电压(KV)/Rate Impulse Voltage(KV)	线芯范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)	可屈/Pitch(mm)	剥线长度/Stripping length(mm)	使用温度范围/Operating temperature(°C)	符合RoHS环保要求/Conform to RoHS	标准颜色编号/Standard color number:	PANTONE / RAL
B	B	III/3	800/24	8.0	0.2~2.5/28~12	5.00	9	-40~+105	Yes	/	/

ITEM	NAME OF PART	MATERIAL	NOTES
3	Current carrier	Copper	Sn Plated
2	Spring	Stainless steel	
1	Housing	PA66	UL94V-0

MATERIAL: /

SURFACE: /

MAT NO.: /  
 STATUS: /  
 APPD: LIGL 2020.05.28  
 CHKD: Mool 2020.05.28  
 DRAFT:ZhengQG 2020.05.28

NAME: **WS2.5-SD-01P-1Y-00A(H)**

DRAWING NO.: WS2.5-SD-C01

REV	ECN	DESCRIPTION	DRAFT	DATE	TYPE	SCALE	REV	SHEET
1					CUSTOMER DRAWING	2:1	T1	1/1

宁波高松电子有限公司  
 NINGBO DEGSON ELECTRICAL CO.,LTD