



公差/General Tolerances(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±1.09	±1.19	±1.60	±2.20	±2.50	±3.15	±4.00
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±1.09	±1.19	±1.60	±2.20	±2.50	±3.15	±4.00

UL 额定电压/Rated Voltage/Current	600V/130A(B/C)
UL 工频耐压/R.M.S withstand voltage	AC220V/1Min
线径范围/Wire range(AWG/mm <sup>2</sup> )	20-20.5-35
线数范围/Poles	N=01-16P
螺丝扭力/Tightening torque(N.m/lb.in)	M8 6.7/60.0
螺丝需松紧-次/Screw tightening once	无/No jammed
使用温度范围/Operating temperature(°C)	-40~+125
剥线长度/Stripping length(mm)	17~18

Note: The A&Z (H) in the name means: A (H) and Z (H).

ITEM	NAME OF PART	MATERIAL	NOTES
9	Tag	PVC	UL94V-0
8	Tramroad	Steel	Zn Plated
7	Fastener	Steel	Zn Plated
6	Screw2	Steel	Zn Plated/M3
5	Current carrier	Copper alloy	NI Plated
4	Housing2	PC	UL94V-0
3	Screw1	Steel	Zn Plated/M8
2	Cover	PC	UL94V-2
1	Housing1	PC	UL94V-0

APPD:	CHKD:	DRAFT:	DATE:
DEGSON		A4	
MATERIAL:	MAT NO./REV:	SURFACE/COLOR:	
	/ 00	MAT STATUS: 批准	

REV	ECN	DESCRIPTION	DRAFT	DATE	DRAWING NO.	TYPE	DRAWING STATUS	SCALE	SHEET
01		更改符号指差			200044195	CUSTOMER DRAWING	work	2:1	4/4

1 2 3 4 5 6