



公差/General Tolerances(mm)		公差/General Tolerances(mm)	
0	>3	>6	>10
~	>3	~	>6
3	6	10	18
±0.12	±0.18	±0.22	±0.26
±0.31	±0.37	±0.57	±0.80
±1.09	±1.15	±1.50	±2.20
±2.50	±2.50	±2.50	±2.50

UL Standard:	B	C	D
额定电压/Rated Voltage(V)/Current(A)	300/20	/	300/10
EC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	/	/
额定电压/电流/Rated Voltage(V)/Current(A)	500/24	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	6.0	/	/
额定扭矩/Torque Tightening(N·m/Lb·in)	M3, 0.5/4.43		
导线范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)	0.2~2.5/28~12		
间距/Pitch(mm)	5.2		
剥线长度/Stripping length(mm)	7-8		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		
标准颜色/Standard color number:			
PANTONE / RAL	/		

MATERIAL:

SURFACE:

MAT NO.:

宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD

STATUS:

NAME: PCMB2.5-01P-1Y-00A(H)

APPD: Li GL 2020.04.03

DRAWING NO.: PCMB2.5-C01

CHKD: Mao J 2020.04.03

SCALE: 2:1

DRT: XDD 2018.11.08

TYPE: CUSTOMER DRAWING

ITEM	NAME OF PART	MATERIAL	NOTES
4	Cage	Copper alloy	M3/Ni-Plated
3	Current Carrier	Copper	Sn Plated
2	Screw	Copper alloy	M3/Ni-Plated
1	Housing	PA66	UL94V-0

REV	ECN	DESCRIPTION	DRT	DATE
1				

SIZE: A4	SIZE: A4	TYPE: CUSTOMER DRAWING	SCALE: 2:1	SHEET 1/1