



精度等级/General		Tolerances/(mm)										公差等级/General					
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/1/10				
1	~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	±Z				
2	~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	±Z				
3	~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	±Z				
4	±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.44	±0.57	±0.70	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±Z

ITEM	NAME OF PART	MATERIAL	NOTES
1	Cover	PA66	UL94V-0
使用温度范围/Operating temperature(°C)			-40~+105
符合RoHS环保要求/Conform to RoHS			Yes
标准颜色编号/Standard color number:			Yes
PANTONE / RAL			/
MATERIAL: SURFACE: /			

MATERIAL:	/
MAT NO.:	/
STATUS:	/
APPD:	Li GL 2020.06.01
CHKD:	Moo J 2020.06.01
DRTI:	Wong LX 2020.06.01
DRAWING NO.: DP-PCKK2.5-C01	
TYPE: CUSTOMER DRAWING	

 **宁波高松电子有限公司**
NINGBO DEGSON ELECTRICAL CO.,LTD
DP-PCKK2.5-01P-1Y-00A(H)

REV	ECN	DESCRIPTION	DRTI	DATE	SIZE: A4	TYPE: CUSTOMER DRAWING	SCALE: 2:1	REV	REV
1								T1	1/1