



公差/General Tolerances(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±Z	∅

3	Screw	Steel	Ni Plated
2	Pin header	Copper alloy	Sn Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:		B	C
UL 标准/UL Standard:		B	C
额定电压/电流/Rated Voltage(V)/Current(A)		300/20	300/20
EC 标准/IEC Standard:		300/20	300/20
过压类别/Overvoltage Category/污染等		III/3	III/2
级/ Pollution Degree		III/3	III/2
额定电压/电流/Rated Voltage(V)/Current(A)		500/32	600/32
额定脉冲电压(kV)/Rate Impulse Voltage(kV)		4	6
额定冲击电压(kV)/Rate Impulse Voltage(kV)		M4, 1.2/10.53	6
螺栓扭矩/Torque Tightening(N.m/Lb.in)		M4, 1.2/10.53	6
线径范围(导线)/Wire Range(Flexible)(AWG)		22~12	
间距/Pitch(mm)/线径范围(Poles)		10.00/N=02~24P	
剥线长度/Stripping length(mm)		9	
使用温度范围/Operating temperature(°C)		-40~+105	
符合RoHS环保要求/Conform to RoHS		Yes	

MATERIAL: / SURFACE: /

NAME: **DEGSON** NINGBO DEGSON ELECTRICAL CO., LTD
 MAT NO.: /
 STATUS: /
 APPD: /
 CHKD: /

DRFT: WU NK 2020.5.26
 DRAWING NO.: DG55H-C04
 TYPE: CUSTOMER DRAWING
 SCALE: 1:1
 SHEET: 1/1

REV	ECN	DESCRIPTION	DRFT	DATE