



公差等级/General	tolerance/(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±1.05	±1.15	±1.60	±2.20	±2.50	±2.50	±2.50	±2.50	±Z

ITEM	NAME OF PART	MATERIAL	NOTES
4	Cage	Steel	M3/Zn Plated
3	Current carrier	Copper	Sn Plated
2	Screw	Steel	M3/Zn Plated
1	Housing	PA66	UL94V-0

REV	ECN	DESCRIPTION	DRAFT	DATE
1				
2				
3				

MATERIAL:	/	SURFACE:	/
MAT NO.:	/	<b>DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD</b>	
STATUS:	/	APPD: Li GL 2020.05.15 CHKD: Moo J 2020.05.15 DRT:Wong LX 2020.05.15	
NAME:	DC4-01P-1Y-00A(H)		
DRAWING NO.:	DC4-C01	TYPE:	CUSTOMER DRAWING
SCALE:	2:1	SHEET	1/1

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	600/30	600/30	600/5
IEC 标准/IEC Standard:	600/30		
过压类别/Overvoltage Category/特类等	III/3		
级/Pollution Degree	/		
额定电压/电涌/Rated Voltage(V)/Current(A)	1000/32	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	8.0	/	/
额定扭矩/Torque Tightening(N·m/Lb.in)	M3, 0.66/6.0	/	/
线径范围(裸线/绞线)/Wire Range(rigid and flexible)(mm²/AWG)	0.5~4/22~10	/	/
侧面/Pitch(mm)	6.1	/	/
剥线长度/Stripping length(mm)	8~9	/	/
使用温度范围/Operating Temperature(°C)	-40~+105	/	/
符合RoHS要求/Conform to RoHS	Yes	/	/
标准颜色编号/Standard color number:	/	/	/
PANTONE / RAL	/	/	/