# ODU AMC<sup>®</sup> REAR PANEL MOUNT RECEPTACLE, SIZE 2, IP6K8 / IP6K9K, 26 CONTACTS, A (LIGHT BROWN) KEY



- Part number
- GK2YAR-P26UC00-000L
- Type of connector Rear panel mount receptacle

2

A (light brown)

5 - 10 mm

• Size


•

- Number of contacts 26
- Keying

**DIMENSIONS:** 

• Cable diameter

POSITIONS: 26 positions











## **Contact Insert Description**

Number of contacts	26
Contact type	Sockets
Contact diameter	0.5 mm
Insulator material	PEEK
Termination type	PCB
Termination diameter	0.5 mm
Reverse gender on request	



#### **Technical information**

Nominal current single contact	5.0 A
Test voltage	0.9 kV DC

IEC 60512-5-2:2002 (DIN EN 60512-5-2:2003) EIA-364-20F:2019-02

All shown connectors are rated to a safety extra low voltage (SELV) of less than 50 V AC / 75 V DC, according to IEC 61140:2016 (VDE 0140-1:2016) Protection against electric shock - Common aspects for installation and equipment. In case other standards rule a specific use of the connector, the application specific safety criteria shall be considered first. In this context, lower voltage ratings may be valid. Warning: Danger to life for operating voltages above 50 V AC / 120 V DC!

#### Mechanical and Environmental data

Degree of protection*	IP6K8 / IP6K9K
Operating temperature	-51°C - 125°C
Mating cycles	5000
*mated condition	

### **Material and Surface Treatments**

Housing Contact Aluminum with ruthenium finish Cu-alloy with gold finish

#### **General information**

All shown connectors are defined without breaking capacity (COC) according to IEC 61984:2008 (VDE 0627:2009).

The respective selected ODU connectors with data transfer functionality can transmit common data transmission such as  $HDMI^{@} 2.0$ ,  $USB^{@} 3.2$  Gen 1x1, FireWire<sup>®</sup> and eSATA<sup>®</sup>, but they are not  $HDMI^{@}$ -,  $USB^{@}$ -, FireWire<sup>®</sup>- and eSATA<sup>®</sup>-standard connectors.

ODU reserves the right to make changes based on the current state of knowledge without prior notice without being obliged to provide replacement deliveries or refinements of older designs.