



精度等级/General Tolerances(mm)												0.1/1/10		
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>280	>315	>400	>500	±Z
3	~ 6	~ 10	~ 18	~ 30	~ 50	~ 80	~ 120	~ 180	~ 280	~ 315	~ 400	~ 500		
±0.12 ±0.18 ±0.22 ±0.26 ±0.31 ±0.37 ±0.57 ±0.80 ±0.93 ±1.05 ±1.15 ±1.60 ±2.20 ±2.50														

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	300/20	/	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/特类等级/Pollution Degree	III/3	/	/
额定电压/电涌/Rated Voltage(V)/Current(A)	500/24	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	6.0	/	/
绕线扭矩/Torque Tightening(N·m/Lb.in)	M3, 0.5/4.5		
线径范围(裸线/带绝缘)/Wire Range(rigid and flexible)(mm²/AWG)	0.2~2.5/24~12		
侧面/Pitch(mm)	5.2		
剥线长度/Stripping length(mm)	8~9		
使用温度范围/Operating Temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number:			
PANTONE / RAL	/		

MATERIAL: SURFACE:

MAT NO.: /

STATUS: /

APPD: Li GL 2020.04.03

CHKD: Mgo J 2020.04.03

DRT: Ding 2017.4.17

DEGSON 宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD

NAME: PCKK2.5-01P-1Y-00A(H)

DRAWING NO.: PCKK2.5-C01

SIZE: A4

mm
inch

TYPE: CUSTOMER DRAWING

SCALE: 1:1 SHEET 1/1

ITEM	NAME OF PART	MATERIAL	NOTES
5	Short carrier fluid	Copper	Sn Plated
4	Screw	Copper alloy	Ni Plated
3	Long carrier fluid	Copper	Sn Plated
2	Cage	Copper alloy	Ni Plated
1	Housing	PA66	UL94V-0

REV	ECN	DESCRIPTION	DRT	DATE
1				
2				
3				
4				