



公差/General Tolerances(mm)		公差/General Tolerances(mm)										公差/General Tolerances(mm)	
0	>3	>5	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	/	/	/
IEC 标准/IEC Standard:	/	/	/
过压类别/Overvoltage Category/特类等	III/3	/	/
额定电压/电涌/Rated Voltage(V)/Current(A)	/	/	/
额定脉冲电压(kV)/Rate Impulse Voltage(kV)	8.0	/	/
绕线扭矩/Torque Tightening(N·m/Lb.in)	M3, 0.5/4.5	/	/
绕线范围(绕线绳规格)/Wire Range(rigid and flexible)(mm ² /AWG)	0.2~2.5/24~12	/	/
剥线长度/Stripping length(mm)	5.2	/	/
使用温度范围/Operating Temperature(°C)	9~10	/	/
符合RoHS要求/Conform to RoHS	-40~+105	/	/
标准颜色编号/Standard color number:	Yes	/	/
PANTONE / RAL	/	/	/

MATERIAL:	/
MAT NO.:	/
STATUS:	/
APPD:	Li GL 2020.04.02
CHKD:	Moo J 2020.04.02
DRT:Wmgq	LX 2020.04.02
SIZE:	A4
TYPE:	CUSTOMER DRAWING
SCALE:	2:1
SHEET:	1/1

NAME: **DEGSON** 宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD

DRAWING NO.: PC2.5-PE-C01

ITEM	NAME OF PART	MATERIAL	NOTES
3	Ground contact		
2	Housing 2	PA66	UL94V-0
1	Housing 1	PA66	UL94V-0

REV	ECN	DESCRIPTION	DRT	DATE

REV	DESCRIPTION	DRT	DATE

1 2 3 4 5 6