



公差表/General Tolerances(mm)														
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/1.0
~	~	~	~	~	~	~	~	~	~	~	~	~	~	±2
3	6	10	18	30	50	80	120	180	250	315	400	500	±2	
±0.12 ±0.18 ±0.22 ±0.26 ±0.31 ±0.37 ±0.57 ±0.80 ±0.93 ±1.05 ±1.15 ±1.60 ±2.20 ±2.50														

5	Spring	Stainless steel
4	Clamp	Copper Alloy
3	Button	PA66
2	Cover	PA66
1	Housing	PA66

UL 标准/UL Standard:	B	C	D
额定电压/电压/Rated Voltage(V)	300/10	300/10	300/10
EC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/ Pollution Degree	III/2		
额定电压/电流/Rated Voltage(V)/Current(A)	320/20		
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	4.0		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm <sup>2</sup> /AWG)	0.2~2.5/26~12		
间距/Pitch(mm)/线数范围/Poles	5.0/02~24P		
剥线长度/Stripping length(mm)	9~10		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number:	/		
PANTONE / RAL	/		

MATERIAL: / SURFACE: /

MAT NO.: /  
 STATUS: /  
 APPD: LIGL 2020.06.16  
 CHKD: MoEK 2020.06.16

NAME: **DEGSON** 宁波高松电子有限公司  
 NINGBO DEGSON ELECTRICAL CO., LTD

DRFT: MEK 2016.04.02  
 TYPE: CUSTOMER DRAWING  
 SCALE: 2:1 SHEET 1/1

REV	ECN	DESCRIPTION	DRFT	DATE