



公差/General Tolerances(mm)	
0	>3
~	>5
3	10
6	18
10	30
±0.22	±0.26
±0.31	±0.37
±0.57	±0.80
±1.05	±1.15
±1.60	±2.20
±2.50	
0.1/1.0	
±Z	

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	600/150	600/150	600/150
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/特等	III/3	/	/
级/Pollution Degree	/	/	/
额定电压/电涌/Rated Voltage(V)/Current(A)	1000/125	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	8.0	/	/
额定扭矩/Torque Tightening(N.m/Lb.in)	M6: 3.5/31		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	2.5~50/14~1/0(Str)		
间距/Pitch(mm)	14~10(Sol)		
剥线长度/Stripping length(mm)	16.0		
使用温度范围/Operating temperature(°C)	14~16		
符合RoHS要求/Conform to RoHS	-40~+105		
标准颜色编号/Standard color number:	Yes		
PANTONE / RAL	/		

MATERIAL: / SURFACE: /

DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD

NAME: DC35-01P-1Y-00A(H)

DRAWING NO.: DC35-C01
 TYPE: CUSTOMER DRAWING
 SCALE: 1:1
 SHEET 1/1

ITEM	NAME OF PART	MATERIAL	NOTES
5	Screw	Steel	M6\Zn Plated
4	Cage	Steel	Zn Plated
3	Current carrier	Copper	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

REV	ECN	DESCRIPTION	DRAFT	DATE
1				
2				
3				
4				

SIZE	DATE	SCALE	SHEET
A4	2020.05.25	1:1	1/1