



尺寸表 (General Dimensions)(mm)													
0	5.3	9.6	9.10	9.18	9.30	9.60	9.120	9.180	9.240	9.315	9.400	0.1/1.0	
3	6	10	18	30	50	80	120	180	250	315	400	500	
+0.2	+0.0	+0.22	+0.28	+0.33	+0.37	+0.57	+0.80	+0.93	+1.05	+1.15	+1.60	+2.20	±2

ITEM	NAME OF PART	MATERIAL	NOTES
1	Housing	PA66	UL94V-0
2	COVER	PA66	UL94V-0
3	Screw	Steel	M3/M4
4	Cage	Copper alloy	Ni Plated
5	Pin	Copper	Sn Plated

UL 标准 / UL Standard:		UL Standard:	材料 / Material
额定电压 / Rated Voltage (V)	Current (A)	300/15	/
额定电流 / Rated Current (A)	Current (A)	300/10	/
过压类别 / Over-voltage Category / 污染等 / Pollution Degree		III/3	III/2
额定电压 / Rated Voltage (V)	Current (A)	400/20	/
额定脉冲电压 (KV) / Rate Impulse Voltage (KV)		/	4
额定扭矩 / Torque Tightening (kg*cm)		M3: 6	/
弹性范围 (弹性系数) / Wire Range (rigid and flexible) (mm ² /AWG)		0.2~2.5	28~12
间距 / Pitch (mm) / 极数 / Poles		7.62	N=02~16P
剥线长度 / Stripping length (mm)		7-8	
使用温度范围 / Operating Temperature (°C)		-40~+105	
符合 RoHS 环保要求 / Conform to RoHS		Yes	

MATERIAL: SURFACE: /

DEGSON[®] NINGBO DEGSON ELECTRICAL CO., LTD

APPD: LanChH 2020.05.18 NAME: 2EDGKR-7.62-XXP-1Y-00A(H)

CHKD: GongZn 2020.05.18 DRAWING NO.: 10002067 REV: 10

PERT: LLY 2020.05.23 TYPE: CUSTOMER DRAWING SCALE: 2:5 SHEET: 1/1

REV	EON	DESCRIPTION	DRT	DATE