



公差/General Tolerances(mm)		公差/General Tolerances(mm)										公差/General Tolerances(mm)	
0	>3	>5	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

ITEM	NAME OF PART	MATERIAL	NOTES
1	Housing	PA66	UL94V-0
2	Button	PA66-GF	UL94V-0
3	Spring	Stainless steel	
4	Current carrier	Copper	Sn plated
5	Grounding	Copper alloy	Sn plated

REV	ECN	DESCRIPTION	DRAFT	DATE
1				
2				
3				

MATERIAL:	SURFACE:
UL Standard:	B C D
额定电压/电涌/Rated Voltage(V)/Current(A)	/ / /
IEC 标准/IEC Standard:	/ / /
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3 / /
额定电压/电涌/Rated Voltage(V)/Current(A)	/ / /
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	6.0 / /
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm <sup>2</sup> /AWG)	0.14~1.5/26~14
间距/Pitch(mm)	3.5
剥线长度/Stripping length(mm)	8~10
使用温度范围/Operating temperature(°C)	-40~+105
符合RoHS标准/Conform to RoHS	Yes

NAME:	NAME:
APPD: Li GL 2020.03.27	APPD: Li GL 2020.03.27
CHKD: Moo J 2020.03.27	CHKD: Moo J 2020.03.27
DRAFT: LiuZH 2019.03.12	DRAFT: LiuZH 2019.03.12
DRAWING NO.: DS1.5-PE-C01	DRAWING NO.: DS1.5-PE-C01
TYPE: CUSTOMER DRAWING	TYPE: CUSTOMER DRAWING
SCALE: 2:1	SCALE: 2:1
SHEET 1/1	SHEET 1/1

DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD  
宁波高松电子有限公司

DS1.5-PE-01P-1C-00A(H)